## **Amendment to the Abstract:**

The Abstract has been amended. A revised Abstract is attached.

An adaptive antenna radio communication device comprises a divided band direction estimating unit (4) for estimating the direction by calculating the cross correlations between a pilot signal and sub-carrier signals of the respective divided bands received by an array antenna (1) and calculating a spatial profile from correlation matrices determined by combining the correlation values between antenna elements of the different sub-carriers according to the output of the cross correlation calculation; a divided band array weight creating unit (5) for creating a weight of a receive array having a directional beam in the direction of estimation for each divided band; and a sub-carrier directivity creating unit (6) for creating a directivity by multiplication-combining the created receive array weight with the corresponding sub-carrier signal. Thus, the accuracy of direction estimation for each divided band can be ensured even in frequency selection fading. Directivity control most suitable for the entire band is made by changing the directivity control method in accordance with the angle spread of the entire band, and multiuser interference is reduced.

Attachment

Kathleen Ligby

lespectfully submitted,

Awrence E. Ashery, Reg. No. 34,515
Attorney for Applicants

LEA/dlm

Attachment: Abstract

Dated: February 10, 2005

The Commissioner for Patents is hereby authorized to charge payment to Deposit Account No. **18-0350** of any fees associated with this communication.

**EXPRESS MAIL** 

Mailing Label Number:

Date of Deposit:

EV 532972805 US February 10, 2005

I hereby certify that this paper and fee are being deposited, under 37 C.F.R. § 1.10 and with sufficient postage, using the "Express Mail Post Office to Addressee" service of the United States Postal Service on the date indicated above and that the deposit is addressed to the Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

## **ABSTRACT**

An adaptive antenna radio communication device comprises a divided band direction estimating unit (4) for estimating the direction by calculating the cross correlations between a pilot signal and sub-carrier signals of the respective divided bands received by an array antenna (1) and calculating a spatial profile from correlation matrices determined by combining the correlation values between antenna elements of the different sub-carriers according to the output of the cross correlation calculation; a divided band array weight creating unit (5) for creating a weight of a receive array having a directional beam in the direction of estimation for each divided band; and a sub-carrier directivity creating unit (6) for creating a directivity by multiplication-combining the created receive array weight with the corresponding sub-carrier signal.